

UNILAND MP HEAVY GREASE

UNILAND MP HEAVY GREASE is a heavy duty, water resistant, multi-purpose grease for automotive and light truck chassis applications. It is formulated with Calcium thickener, rust and oxidation inhibiting additives.

APPLICATION

UNILAND MP HEAVY GREASE is suitable for a wide variety of lubrication use. Recommended for motor vehicles & farm tractors chassis & suspension systems lubrication points, ball, shaft & universal joints and coil springs. Suitable for general automotive, industrial and agricultural lubrication of equipment, machine parts and automotive wheel bearings. Provides maximum protection against rust and corrosion with chassis that is exposed to severe water exposure. Protects against moisture contamination with excellent water resistance. Prevent dust and dirt from reaching into the moving parts. This product is recommended operating temperature range is -5°C to 105°C.

APPLICATION BENEFITS

UNILAND MP HEAVY GREASE provides:

- Significantly less rust & corrosion due to effective protection from severe water exposure.
- Longer suspension, ball, shaft & universal joints and coil springs life due to low wear.
- Calcium based, making it compatible with most of the grease used for chassis.
- Excellent resistance to water washout.
- No softening/ leakage under vibrations & mechanical stress due to good mechanical stability.

TECHNICAL CHARACTERISTICS

Technical property	Method	RESULTS	
NLGI grade	-	2.0	3.0
Thickener Type	-	Calcium Soap	Calcium Soap
Dropping point, °C	ASTM D-2265	120	120
Colour	-	RED	RED
Worked Penetration	ASTM D-217	265-295	250-265
Rust and Corrosion Test	ASTM D-1743	PASS	PASS
Water Wash-Out	ASTM D-1264	PASS	PASS
Texture	-	Smooth	Smooth

Due to continual product research and development, the information contained herein is subject to change without notification.
© 2015 UNIMARINE PTE LTD, SINGAPORE.