

UNILAND AEROMAX SP 5W-40 A3/B4

UNILAND AEROMAX SP 5W-40 A3/B4 is a scientifically developed gasoline engine oil, advanced full synthetic engine oil delivers outstanding engine Performance, Protection, and Cleanliness. UNILAND AEROMAX SP 5W-40 A3/B4 helps your engine perform at its best.

APPLICATION

UNILAND AEROMAX SP 5W-40 A3/B4 is suitable for use in automobile, gasoline and diesel engines where the manufacturer recommends an ACEA A3/B3, A3/B4, API SP, SN/CF or earlier specification 5W-40 lubricant.

APPLICATION BENEFITS

UNILAND AEROMAX SP gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring a high level of protection and low viscosity oils.

UNILAND AEROMAX SP 5W-40 provides:

- Maximises short- and long-term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperature
- Independently proven to Improve engine efficiency
- Delivers and sustains maximum horsepower for longer, even when under pressure

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-40
Density at 15°C	ASTM D-4052	0.8530
Flash point, °C	ASTM D-92	210
Viscosity, CCS -30C (5W)	ASTM D-5293	5930
Pour point, °C	ASTM D-97	-39
Viscosity index	ASTM D-2270	167
Kinematic viscosity at 40°C (cSt)	ASTM D-445	85
Kinematic viscosity at 100°C (cSt)	ASTM D-445	13.7

SPECIFICATIONS / APPROVALS

- ACEA A3/B3, A3/B4
- API SP, SN/CF
- BMW Longlife-01
- MB-Approval 226.5/ 229.3/ 229.5
- Porsche A40
- Renault RN0700 / RN0710
- VW 502 00/ 505 00

Due to continual product research and development, the information contained here is subject to change without notification.

© 2014 UNIMARINE PTE. LTD, SINGAPORE

UNIMARINE PTE. LTD.

1 Raffles Place #26-01A One Raffles Place (Tower One) Singapore 048616
 Phone: + 6022 5290 Email: marinelubs@unimarine-lubricants.com